

J60 Series UPS Price List

*For the most current pricing, visit www.xpcc.com/pricing

Lithium Ion UPS 350VA, 600VA
120VAC or 230VAC

Protect digital signage, kiosks and POS from power outages with an ultra-slim J60 UPS

- › Lithium batteries provide protection for up to 15 years or 3,000 - 5,000 cycles
- › Operates to 50 °C (122 °F), derates above 40 °C
- › Power outage protection – up to 7 minutes at full load
- › UL or CE, RoHS, TAA compliant
- › 5 years warranty (USA & Canada) - 2 years when temps are above 40°C (104°F) and below 50°C (122°F).



J60 Series UPS 120V 50/60Hz

Model	Part Number	Description	List Price	Input Power Cord	Output Receptacles	Unit Weight	Unit Dimensions (W x D x H)
J60-350	90000465	350VA/200W 120V UPS	\$489.00	IEC C13 to 5-15P, 3 ft	(3) 5-15R	3.4 lbs	6.9" x 8.5" x 1.25"
J60-600	90000776	600VA/360W 120V UPS	\$819.00	IEC C13 to 5-15P, 3 ft	(3) 5-15R	4.7 lbs	7.3" x 10.8" x 1.6"

J60i Series UPS 230VAC 50/60Hz

Model	Part Number	Description	List Price	Input Power Cord	Output Receptacles	Unit Weight	Unit Dimensions (W x D x H)
J60i-350	90000472	350VA/200W 230V UPS	\$489.00	IEC C14 inlet	(2) IEC C13	3.4 lbs	6.9" x 8.5" x 1.25"
J60i-600	90000777	600VA/360W 230V UPS	\$819.00	IEC C14 inlet	(2) IEC C13	4.7 lbs	7.3" x 10.8" x 1.6"

J60 Accessories

Model	Part Number	Description	List Price	Unit Weight
XPC-515P-3RA	N/A	3ft line cord with offset, right angle 5-15P for use with J60-350/600	\$22.00	1 lbs
XPC-515P-6RA	N/A	6ft line cord with offset, right angle 5-15P for use with J60-350/600	\$22.00	1 lbs
SNMP-J60	90000778	J60-600(i) external SNMP card	\$320.00	1 lb
EMD-J60	90000785	Environmental monitoring device for use with SNMP-J60*	\$250.00	1 lb
JX-200	90000742	200W Isolation transformer matching J60-350 dimensions	\$240.00	7 lbs
J60-DIN	90000765	DIN rail mount kit for J60	\$21.00	2 lbs

*EMD-J60 must be used with the SNMP-J60

Standard 5 Year Factory Warranty – (USA & Canada) 5 years electronics/battery. Telephone technical support. Depot exchange. Ground shipment one way.

Standard 3 Year Factory Warranty – (Outside USA & Canada) 3 years electronics/battery. Telephone technical support. Depot exchange. Ground shipment one way.

BATTERY RUNTIMES

System Load (watts)	30	40	80	120	160	200	240	280	320	360
J60/J60i-350	43	32	17	11	9	7	N/A	N/A	N/A	N/A
J60/J60i-600	86	64	35	23	17	14	11	9	8	6

(Runtimes are shown in minutes and will vary based on battery age and site conditions.)