

TX91L 3.8kVA-10kVA Series UPS Price List

*For the most current pricing, visit www.xpcc.com/pricing

Isolated Online 3.8kVA-10kVA

208VAC Input // 240/120VAC or 230/115VAC Output

Isolated online UPS provides protection from all 10 common power problems

- › Available models: 3.8kVA/3.8kW, 5kVA/5kW, 6kVA/6kW, 10kVA/10kW
- › Powerful 4A charger for use with large external battery systems
- › Maintenance bypass
- › Galvanic isolation transformer
- › Configurable outputs
- › Auto restart
- › UL1778, cUL, FCC Class A, RoHS, TAA compliant (UPS only)
- › 3 years electronics (USA and Canada)



TX91L 3.8kVA 208VAC Input - **240/120VAC or 230/115VAC Output Pricing

TX91L series have a 4A charger with no internal batteries.

Model	Part Number	Description	List Price	Input Connection	Output Connection	Shipping Weight	Unit Dimensions (W x D x H)
TX91L-3.8K	90000587	3.8kVA/3.8kW Tower UPS with Isolation Transformer	\$5,610.00	Terminal block	Terminal block	152 lbs	9.8" x 23.2" x 32.4"
TX91L-3.8KB1#####	Bundle	3.8kVA/3.8kW Tower UPS with Isolation Transformer	\$7,077.00	L6-30P, 6ft	(6) Configurable 240V outputs* + (4) 5-15/20R	157 lbs	9.8" x 27.1" x 32.4"
TX91L-3.8KB2#####	Bundle	3.8kVA/3.8kW Tower UPS with Isolation Transformer	\$7,077.00	L6-30P, 6ft	(4) Configurable 240V outputs* + (4) 5-15/20R + (1) L6-30R	157 lbs	9.8" x 27.1" x 32.4"

*Replace the "#####" in the model number with four of the letters shown below. Each configurable output is protected by a 20A breaker. 240V/230V: A. L6-20R; B. L6-30R; C. 6-15/20R; D. L6-15R (non-locking C20) **For optional voltage configurations add \$300 list (PN:T9VCNFG, see below)

TX91L 5kVA 208VAC Input - **240/120VAC or 230/115VAC Output Pricing

TX91L series have a 4A charger with no internal batteries.

Model	Part Number	Description	List Price	Input Connection	Output Connection	Shipping Weight	Unit Dimensions (W x D x H)
TX91L-5K	90000588	5kVA/5kW Tower UPS with Isolation Transformer	\$6,655.00	Terminal block	Terminal block	155 lbs	9.8" x 23.3" x 32.4"
TX91L-5KB1#####	Bundle	5kVA/5kW Tower UPS with Isolation Transformer	\$8,122.00	L6-30P, 6ft	(6) Configurable 240V outputs* + (4) 5-15/20R	160 lbs	9.8" x 27.1" x 32.4"
TX91L-5KB2#####	Bundle	5kVA/5kW Tower UPS with Isolation Transformer	\$8,122.00	L6-30P, 6ft	(4) Configurable 240V outputs* + (4) 5-15/20R + (1) L6-30R	160 lbs	9.8" x 27.1" x 32.4"

*Replace the "#####" in the model number with four of the letters shown below. Each configurable output is protected by a 20A breaker. 240V/230V: A. L6-20R; B. L6-30R; C. 6-15/20R; D. L6-15R (non-locking C20) **For optional voltage configurations add \$300 list (PN:T9VCNFG, see below)

TX91L 6kVA 208VAC Input - **240/120VAC or 230/115VAC Output Pricing

TX91L series have a 4A charger with no internal batteries. 6kVA system capacity will be reduced by 30A input circuit

Model	Part Number	Description	List Price	Input Connection	Output Connection	Shipping Weight	Unit Dimensions (W x D x H)
TX91L-6K	90000589	6kVA/6kW Tower UPS with Isolation Transformer	\$7,480.00	Terminal block	Terminal block	158 lbs	9.8" x 23.3" x 32.4"
TX91L-6KB1#####	Bundle	6kVA/6kW Tower UPS with Isolation Transformer	\$8,789.00	L6-30P, 6ft	(6) Configurable 240V outputs* + (4) 5-15/20R	163 lbs	9.8" x 27.1" x 32.4"
TX91L-6KB2#####	Bundle	6kVA/6kW Tower UPS with Isolation Transformer	\$8,789.00	L6-30P, 6ft	(4) Configurable 240V outputs* + (4) 5-15/20R + (1) L6-30R	163 lbs	9.8" x 27.1" x 32.4"

*Replace the "#####" in the model number with four of the letters shown below. Each configurable output is protected by a 20A breaker. 240V/230V: A. L6-20R; B. L6-30R; C. 6-15/20R; D. L6-15R (non-locking C20) **For optional voltage configurations add \$300 list (PN:T9VCNFG, see below)

TX91L 10kVA 208VAC Input - **240/120VAC or 230/115VAC Output Pricing

TX91L series have a 4A charger with no internal batteries.

Model	Part Number	Description	List Price	Input Connection	Output Connection	Shipping Weight	Unit Dimensions (W x D x H)
TX91L-10K	90000590	10kVA/10kW Tower UPS with Isolation Transformer	\$10,164.00	Terminal block	Terminal block	187 lbs	9.8" x 23.3" x 32.4"
TX91L-10KB1####	Bundle	10kVA/10kW Tower UPS with Isolation Transformer	\$11,473.00	Terminal block	(6) Configurable 240V outputs* + (4) 5-15/20R	192 lbs	9.8" x 27.1" x 32.4"
TX91L-10KB2####	Bundle	10kVA/10kW Tower UPS with Isolation Transformer	\$11,473.00	Terminal block	(4) Configurable 240V outputs* + (4) 5-15/20R + (1) L6-30R	192 lbs	9.8" x 27.1" x 32.4"

*Replace the "####" in the model number with four of the letters shown below. Each configurable output is protected by a 20A breaker.

240V/230V: A. L6-20R; B. L6-30R; C. 6-15/20R; D. L6-15R (non-locking C20) **For optional voltage configurations add \$300 list (PN:T9VCNFG, see below)

Custom Voltage Configurations

Model	Part Number	Description	List Price
T9VCNFG	90000375	Preconfigure TX91L Transformer and Electronics for Custom Voltage Configuration, Input:Output Voltages Available: 240V:240/120V, 230V:230/115V, 220V:220/110V	\$300.00

TX91 Battery Options

Battery packs not for use with "XR" models.

Model	Part Number	Description	List Price	Shipping Weight	Unit Dimensions (W x D x H)
TX91-BP960-1	90000584	Extended Battery Pack for TX91 with (20) 12V 9AH Batteries	\$3,740.00	190 lbs	9.8" x 22.3" x 32.4"
TX91-BP960-2	90000585	Extended Battery Pack for TX91 with (40) 12V 9AH Batteries	\$5,390.00	320 lbs	9.8" x 22.3" x 32.4"
TX91-BP960-3	90000586	Extended Battery Pack for TX91 with (60) 12V 9AH Batteries	\$7,095.00	450 lbs	9.8" x 22.3" x 32.4"

TX91L Connectivity

Model	Part Number	Description	List Price	Unit Weight	Shipping Dimensions (W x D x H)
SNMP-2PV3	90000741	Two Port Internal SNMP Card	\$389.00	1 lb	7.25" x 6" x 2.5"
SNMP-EMPV2*	90000674	Environmental Monitoring Sensor	\$230.00	1 lb	7.25" x 6" x 2.5"
MODBUS-IN	90000267	Modbus Card	\$319.00	1 lb	7.25" x 6" x 2.5"
RELAY-MINI	90000265	General Relay Contacts with DB9 & Terminal Block Adapter	\$120.00	1 lb	7.25" x 6" x 2.5"

*SNMP-EMPV2 must be used with SNMP-2PV3

TXVR Output Cords

Model	Description	Cord Length	Input Voltage	List Price	Unit Weight
XPC-ZLC20-620R	Locking IEC C20 to 6-15/20R	1ft	208/230V	\$79.00	3 lbs
XPC-ZLC20-L620R	Locking IEC C20 to L6-20R	1ft	208/230V	\$79.00	3 lbs
XPC-ZLC20-L630R	Locking IEC C20 to L6-30R	1ft	208/230V	\$79.00	3 lbs
XPC-C20-L615R	Non-locking IEC C20 to L6-15R	1ft	208/230V	\$59.00	3 lbs

Power Distribution Units

Model	Part Number	Description	List Price	Input Power Cord	Outlets	Unit Weight	Unit Dimensions (W x D x H)
XPD31	90000251	30A 240V 2U 19" Basic Rack PDU	\$580.00	L6-30P, 6ft	(2) L6-30R + (2) L6-20R + (4) 6-15/20R	9.0 lbs	19.0" x 4.7" x 3.5"
XPD32	90000252	30A 240V 2U 19" Basic Rack PDU	\$580.00	L6-30P, 6ft	(2) L6-30R + (4) L6-20R	7.5 lbs	19.0" x 2.4" x 3.5"
XPD33	90000253	30A 240V 2U 19" Basic Rack PDU	\$450.00	L6-30P, 6ft	(4) IEC C19 + (8) IEC C14	6 lbs	19.0" x 2.4" x 3.5"
XPD34	90000254	30A 240/120V 2U 19" Basic Rack PDU	\$690.00	L14-30P, 6ft	(2) L6-30R + (4) L6-20R + (12) 5-15/20R	9.5 lbs	19.0" x 4.7" x 3.5"
XPD38	90001037	30A 120V 2U 19" Basic Rack PDU	\$690.00	L14-30P, 6ft	(4) L5-30R + (4) L5-20R	9.5 lbs	19.0" x 4.7" x 3.5"

TX91L Startup/Service Plans (USA and Canada)

On-site service within 100 miles of an Xtreme Power Service Technician. Contact inside sales for locations exceeding 100 miles.

Model	Part Number	Description	List Price
9SUS8051	90001282	Startup 5x8 and 1 year on-site warranty	\$3,900.00
9SUS8052	90001283	Startup 5x8 and 2 year on-site warranty	\$4,500.00
9SUS8053	90001284	Startup 5x8 and 3 year on-site warranty	\$5,100.00
9SU724051	90001285	Startup 7x24 and 1 year on-site warranty	\$5,070.00
9SU724052	90001286	Startup 7x24 and 2 year on-site warranty	\$5,850.00
9SU724053	90001287	Startup 7x24 and 3 year on-site warranty	\$6,630.00
9PM58	90001288	Preventative maintenance service, 5x8	\$3,500.00
9PM724	90001289	Preventative maintenance service, 7x24	\$4,550.00
SVCADD	90000538	Service addder for locations further than 100 miles	\$1,050
T9SP610	90000453	Extended 5 Year Factory Warranty for TX91L	\$1,500.00
T9SPBP2	90000454	Extended 5 Year Factory Warranty for TX91-BP960-1	\$950.00
T9SPBP4	90000455	Extended 5 Year Factory Warranty for TX91-B960-2	\$1,000.00
T9SPBP6	90000456	Extended 5 Year Factory Warranty for TX91-B960-3	\$1,300.00

Standard 3 Year Factory Warranty – 3 years electronics/battery. Telephone technical support. Depot exchange. Ground shipment one way.

On-site 3 Year Service Plan – 3 year on-site service. On-site startup. On-site corrective maintenance. Services performed 5 x 8.

Extended 5 Year Factory Warranty – 5 year electronics/battery. Telephone technical support. Advanced exchange. Pricing is limited to the continental USA. Ground shipment both ways.

On-site 5 Year Service Plan – 5 year on-site service. On-site startup. On-site corrective maintenance. Services performed 5 x 8.

TX91L Battery Runtimes

Runtimes are shown in minutes and will vary based on battery condition, age, cycles, and ambient temperature.

Model	BP960-1		BP960-2		BP960-3		BP960-1 + BP960-3		BP960-2 + BP960-3		(2) BP960-3		BP960-1 + (2) BP960-3		BP960-2 + (2) BP960-3	
Percentage load:	50%	100%	50%	100%	50%	100%	50%	100%	50%	100%	50%	100%	50%	100%	50%	100%
TX91L-3.8K	37	16	92	38	140	65	198	94	259	120	322	144	404	173	468	203
TX91L-5K	26	11	64	27	106	45	142	66	186	90	232	109	279	127	328	146
TX91L-6K	20	8	50	21	87	36	119	52	150	70	186	90	224	106	263	122
TX91L-10K	9	3	24	11	40	18	58	27	80	36	97	45	116	55	131	66

For extended runtimes and detailed requirements, see www.xpcc.com/selector