

J90 Series UPS Price List

*For the most current pricing, visit www.xpcc.com/pricing

**Lithium Ion UPS 1kVA-3kVA
120VAC**

Protect critical servers and network devices from spikes, surges and power outages with online 1U J90 UPS

- › LFP battery providing up to 15 years or 3,000–5,000 discharge cycles
- › Switched receptacles allowing remote on/off control of each outlet
- › Power outage protection with up to 7 minutes at full load
- › Easy-to-read LCD display for status and diagnostics
- › Standard wall mount or optional rack-mount kit
- › Extended battery options available for 2 kVA and 3 kVA models
- › Compliance with UL, cUL, FCC A, UN38.3, CE, RoHS, TAA Compliant
- › Six-year electronics and six-year battery warranty (USA & Canada)
- › High-temperature performance rated for operation up to 50°C (122°F)



J90 Series UPS 120V 50/60Hz

Model	Part Number	Description	List Price	Input Power Cord	Output Receptacles	Unit Weight	Unit Dimensions (W x D x H)
J90-1kLiD	90001298	1000VA/900W 120V UPS, 6.5 min battery	\$2,500.00	C14 inlet, 5ft 5-15P to C13	(4) 5-15R, all are switchable via Web/SNMP Card	27.3 lbs	17.2 x 18.8 x 1.7 in
J90-1.5kLiD	90001301	1500VA/1350W 120V UPS 7 min battery	\$2,880.00	6ft 5-15P	(4) 5-15R all are switchable via Web/SNMP Card	27.8 lbs	17.2 x 20 x 1.7 in
J90-2kLiD	90001310	2000VA/1800W 120V UPS 6 min battery, Optional external battery pack	\$4,250.00	6ft 5-20P	(4) 5-20R all are switchable via Web/SNMP Card	34.1 lbs	17.2 x 22.8 x 1.7 in
J90-3kLiD	90001312	3000VA/2700W 120V UPS 4 min battery, Optional external battery pack	\$5,100.00	6ft L5-30P	(3) 5-20R and (1) L5-30R, all are switchable	35.2 lbs	17.2 x 22.8 x 1.7 in

External Battery Pack

Model	Part Number	Description	List Price	Unit Weight	Unit Dimensions (W x D x H)
J90-EBP48	90001314	20AH 48V DC Lithium Iron Phosphate Battery for J90-2kLi and J90-3kLi	\$3,700.00	30.8 lbs	17.2 x 22.8 x 1.7 in

J90 Connectivity

Model	Part Number	Description	List Price	Unit Weight	Shipping Dimensions (W x D x H)
SNMP-2PV3	90000741	Two Port Internal SNMP Card	\$389.00	1 lb	7.25" x 6" x 2.5"
SNMP-EMPV2*	90000674	Environmental Monitoring Sensor	\$230.00	1 lb	7.25" x 6" x 2.5"
RELAY-MINI	90000265	General Relay Contacts with DB9 & Terminal Block Adapter	\$120.00	1 lb	7.25" x 6" x 2.5"

*SNMP-EMPV2 to be used with SNMP-2PV3

Bypass Distribution Modules

Model	Part Number	Description	List Price	Utility Input	Output Connections	UPS Connections	Unit Weight	Unit Dimensions (W x D x H)
XBDM-1015LV	90000090	Bypass 15A/120VAC for use with J90-1.5kLi	\$465.00	5–15P, 12ft	(6) 5–15R front (4) 5–15R back	5-15R	3.4 lbs	19" x 3.5" x 1.75"
XBDM-1020LV	90000091	Bypass 20A/120VAC for use with J90-2kLi	\$490.00	5–20P, 12ft	(6) 5–20R front (4) 5–20R back	5-20R	3.4 lbs	19" x 3.5" x 1.75"
XBDM-1030LV	90000093	Bypass 30A/120VAC for use with J90-3kLi	\$830.00	L5–30P, 6ft	(6) 5–20R front (4) 5–20R back	L5-30R	3.4 lbs	19" x 3.5" x 1.75"

Power Distribution Units & Transformers

Model	Part Number	Description	List Price	Input Power Cord	Outlets	Unit Weight	Unit Dimensions (W x D x H)
XPD-1415HV	90000041	120V Basic Power Distribution Unit	\$135.00	5–15P, 12ft	(14) 5–15R	3.5 lbs	19.0" x 3.5" x 1.75"
XPD-1420HV	90000045	120V Basic Power Distribution Unit	\$155.00	L5–20P, 12ft or 5–20P with adapter	(14) 5–20R	4.8 lbs	19.0" x 3.5" x 1.75"

J90 Mounting Kits

Model	Part Number	Description	List Price	Unit Weight	Unit Dimensions (W x D x H)
P90-RAIL	90000909	4-Post Rail Kit	\$148.50	5 lbs	3.8" x 19.8" x 2.8"
XPC-2PRAIL	90000406	2-Post Rail Kit; Rated for 125 lbs	\$102.00	5 lbs	4.0" x 20.0" x 3.0"
XPC-2POSTL	90000116	2-Post Shelf Kit; Rated for 150 lbs	\$160.00	9 lbs	21.5" x 23.3" x 3.5"
XPC-2PRLV2	90001273	2-Post 2U Center Mount with Front Ears; Rated for 160 lbs	\$225.00	11 lbs	16" x 15" x 9"

BATTERY RUNTIMES

UPS Load (VA)	100	150	200	300	400	600	800	1000	1200	1400	1500	1600	1800	2000	2333	2667	3000
UPS Load (Watts)	90	135	180	270	360	540	720	900	1080	1260	1350	1440	1620	1800	2100	2400	2700
J90-1kLiD	53	35	30	21	16	11	8.1	6.5	-	-	-	-	-	-	-	-	-
J90-1.5kLiD	-	59	44	33	24	17	13	10.5	8.8	7.5	7	-	-	-	-	-	-
J90-2kLiD	-	-	54	36	28	20	15	12	10	8.6	8	7.5	6.7	6	-	-	-
J90-2kLiD + 1 EBP48	-	-	270	180	142	100	75	60	50	43	40	38	33	30	-	-	-
J90-2kLiD + 2 EBP48	-	-	486	324	255	180	135	108	90	77	72	68	60	54	-	-	-
J90-2kLiD + 3 EBP48	-	-	703	468	368	260	195	156	130	111	104	98	87	78	-	-	-
J90-2kLiD + 4 EBP48	-	-	919	613	481	340	255	204	170	146	136	128	113	102	-	-	-
J90-2kLiD + 5 EBP48	-	-	1135	757	594	420	315	252	210	180	168	158	140	126	-	-	-
J90-2kLiD + 6 EBP48	-	-	1351	901	708	500	375	300	250	214	200	188	167	150	-	-	-
J90-3kLiD	-	-	-	38	28	20	15	12	10	8.6	8	7.5	6.7	6	5.1	4.5	4
J90-3kLiD + 1 EBP48	-	-	-	189	142	98	73	60	50	43	40	38	33	30	26	23	20
J90-3kLiD + 2 EBP48	-	-	-	341	256	176	132	108	90	77	72	68	60	54	46	41	36
J90-3kLiD + 3 EBP48	-	-	-	492	369	254	191	156	130	111	104	98	87	78	67	59	52
J90-3kLiD + 4 EBP48	-	-	-	644	483	333	249	204	170	146	136	128	113	102	87	77	68
J90-3kLiD + 5 EBP48	-	-	-	795	596	411	308	252	210	180	168	158	140	126	108	95	84
J90-3kLiD + 6 EBP48	-	-	-	946	710	489	367	300	250	214	200	188	167	150	129	113	100

(Runtimes are shown in minutes and will vary based on battery age and site conditions.)

J90 Advanced Exchange Warranty Upgrade

Model	Part Number	Description	List Price
P91ADVEX	90001036	Advanced Exchange Warranty Upgrade - Advanced Warranty Exchange and Shipping for P91Li or J90/J90i UPS	\$250.00

Standard 6 Year Factory Warranty – 6 years electronics/battery. Telephone technical support. Depot exchange. Ground shipment one way

Advanced Warranty Exchange – 6 years electronics/battery. Telephone technical support. Advanced warranty exchange. Ground shipment both ways. Pricing is limited to the continental USA