

**J90i Series UPS Price List**

\*For the most current pricing, visit [www.xpcc.com/pricing](http://www.xpcc.com/pricing)

**Lithium Ion UPS 1kVA-3kVA**  
208/230VAC

**Protect critical loads with the online 1U J90i UPS**

- › LFP battery providing up to 15 years or 3,000–5,000 discharge cycles
- › Switched receptacles allowing remote on/off control of each outlet
- › Power outage protection with up to 7 minutes at full load
- › Easy-to-read LCD display for status and diagnostics
- › Standard wall mount or optional rack-mount kit
- › Extended battery options available for 2 kVA and 3 kVA models
- › Compliance with UN38.3, CE, RoHS, TAA Compliant
- › Six-year electronics and six-year battery warranty (USA & Canada)
- › High-temperature performance rated for operation up to 50°C (122°F)



**J90i Series UPS 230V 50/60Hz**

Model	Part Number	Description	List Price	Input Power Cord	Output Receptacles	Unit Weight	Unit Dimensions (W x D x H)
J90i-1kLiD	90001299	1000VA/900W 208/230V UPS, 6.5 min battery	\$2,450.00	C14 Inlet	(4) IEC C13, all are switchable via Web/SNMP Card	26.8 lbs (12.2 kg)	17.2 x 18.8 x 1.7 in (437 x 478 x 43.2 mm)
J90i-1.5kLiD	90001302	1500VA/1350W 208/230V UPS, 7 min battery	\$2,830.00	C14 Inlet	(4) IEC C13, all are switchable via Web/SNMP interface	27.4 lbs (12.4 kg)	17.2 x 20 x 1.7 in (437 x 508 x 43.2 mm)
J90i-2kLiD	90001311	2000VA/1800W 208/230V UPS, 6 min battery, Optional external battery pack	\$4,100.00	C20 inlet	(4) IEC C13 all are switchable via via Web/SNMP interface	34.1 lbs (15.5 kg)	17.2 x 22.8 x 1.7 in (437 x 579 x 43.2 mm)
J90i-3kLiD	90001313	3000VA/2700W 208/230V UPS, 4 min battery, Optional external battery pack	\$4,950.00	C20 inlet	(3) C13 and (1) C19, all switchable via Web/SNMP interface	35.2 lbs (16 kg)	17.2 x 22.8 x 1.7 in (437 x 579 x 43.2 mm)

**External Battery Pack (J90i-2kLi, J90i-3kLi)**

Model	Part Number	Description	List Price	Unit Weight	Unit Dimensions (W x D x H)
J90-EBP48	90001314	20AH 48V DC Lithium Iron Phosphate Battery for J90i-2kLi and J90i-3kLi	\$3,700.00	30.8 lbs (14 kg)	17.2 x 22.8 x 1.7 in (437 x 579 x 43.2 mm)

**J90i Connectivity**

Model	Part Number	Description	List Price	Unit Weight	Shipping Dimensions (W x D x H)
SNMP-2PV3	90000741	Two Port Internal SNMP Card	\$389.00	1 lb	7.25" x 6" x 2.5"
SNMP-EMPV2*	90000674	Environmental Monitoring Sensor	\$230.00	1 lb	7.25" x 6" x 2.5"
RELAY-MINI	90000265	General Relay Contacts with DB9 & Terminal Block Adapter	\$120.00	1 lb	7.25" x 6" x 2.5"

\*SNMP-EMPV2 to be used with SNMP-2PV3

**Bypass Distribution Modules**

Model	Part Number	Description	List Price	Utility Input	Output Connections	UPS Connections	Unit Weight	Unit Dimensions (W x D x H)
XBDM1020HV1	90000092	Bypass 16A capacity. Includes (1) IEC C14-C19 cable and (1) C20 to C13 cable	\$495.00	IEC C20 inlet	(2) IEC C19 + (4) IEC C13 front (4) IEC C13 back	IEC C20	3.5 lbs	19.3" x 3.5" x 1.75"
XBDM1020HV2	90000094	Bypass 16A capacity. Includes (2) IEC C19-C20 cord kit	\$495.00	IEC C20 inlet	(2) IEC C19 + (4) IEC C13 front (4) IEC C13 back	IEC C20	3.5 lbs	19.3" x 3.5" x 1.75"

**Power Distribution Units & Transformers**

Model	Part Number	Description	List Price	Input Power Cord	Outlets	Unit Weight	Unit Dimensions (W x D x H)
XPDU-IEC	90000053	230V Basic Power Distribution Unit	\$205.00	IEC C20 inlet	(10) IEC C13 + (2) IEC C19	2.6 lbs	19.0" x 3.5" x 1.75"
XAT-400	90000269	400VA Step Down Transformer 208V to 120V	\$660.00	208V IEC C14, 2ft	120V 5-15R, 2ft	8 lbs	7.0" x 6.8" x 5.9"
XPD-IT15A	90000739	1.5kW Transformer PDU 208V to 120V	\$1,090.00	Detachable 3 ft, C14 to C13 Cord	(16) 5-15R	43 lbs	17.3 x 10.5 x 3.5 in (2U)

**J90i Mounting Kits**

Model	Part Number	Description	List Price	Unit Weight	Unit Dimensions (W x D x H)
P90-RAIL	90000909	4-Post Rail Kit	\$135.00	5 lbs	3.8" x 19.8" x 2.8"
XPC-2PRAIL	90000406	2-Post Rail Kit; Rated for 125 lbs	\$102.00	5 lbs	4.0" x 20.0" x 3.0"
XPC-2POSTL	90000116	2-Post Shelf Kit; Rated for 150 lbs	\$160.00	9 lbs	21.5" x 23.3" x 3.5"
XPC-2PRLV2	90001273	2-Post 2U Center Mount with Front Ears; Rated for 160 lbs	\$225.00	11 lbs	16" x 15" x 9"

**BATTERY RUNTIMES**

UPS Load (VA)	100	150	200	300	400	600	800	1000	1200	1400	1500	1600	1800	2000	2333	2667	3000
UPS Load (Watts)	90	135	180	270	360	540	720	900	1080	1260	1350	1440	1620	1800	2100	2400	2700
J90i-1kLiD	53	35	30	21	16	11	8.1	6.5	-	-	-	-	-	-	-	-	-
J90i-1.5kLiD	-	59	44	33	24	17	13	10.5	8.8	7.5	7	-	-	-	-	-	-
J90i-2kLiD	-	-	54	36	28	20	15	12	10	8.6	8	7.5	6.7	6	-	-	-
J90i-2kLiD + 1 EBP48	-	-	270	180	142	100	75	60	50	43	40	38	33	30	-	-	-
J90i-2kLiD + 2 EBP48	-	-	486	324	255	180	135	108	90	77	72	68	60	54	-	-	-
J90i-2kLiD + 3 EBP48	-	-	703	468	368	260	195	156	130	111	104	98	87	78	-	-	-
J90i-2kLiD + 4 EBP48	-	-	919	613	481	340	255	204	170	146	136	128	113	102	-	-	-
J90i-2kLiD + 5 EBP48	-	-	1135	757	594	420	315	252	210	180	168	158	140	126	-	-	-
J90i-2kLiD + 6 EBP48	-	-	1351	901	708	500	375	300	250	214	200	188	167	150	-	-	-
J90i-3kLiD	-	-	-	38	28	20	15	12	10	8.6	8	7.5	6.7	6	5.1	4.5	4
J90i-3kLiD + 1 EBP48	-	-	-	189	142	98	73	60	50	43	40	38	33	30	26	23	20
J90i-3kLiD + 2 EBP48	-	-	-	341	256	176	132	108	90	77	72	68	60	54	46	41	36
J90i-3kLiD + 3 EBP48	-	-	-	492	369	254	191	156	130	111	104	98	87	78	67	59	52
J90i-3kLiD + 4 EBP48	-	-	-	644	483	333	249	204	170	146	136	128	113	102	87	77	68
J90i-3kLiD + 5 EBP48	-	-	-	795	596	411	308	252	210	180	168	158	140	126	108	95	84
J90i-3kLiD + 6 EBP48	-	-	-	946	710	489	367	300	250	214	200	188	167	150	129	113	100

*(Runtimes are shown in minutes and will vary based on battery age and site conditions.)*

**J90i Advanced Exchange Warranty Upgrade**

Model	Part Number	Description	List Price
P91ADVEX	90001036	Advanced Exchange Warranty Upgrade - Advanced Warranty Exchange and Shipping for P91Li or J90i/J90ii UPS	\$250.00

**Standard 6 Year Factory Warranty** – 6 years electronics/battery. Telephone technical support. Depot exchange. Ground shipment one way

**Advanced Warranty Exchange** – 6 years electronics/battery. Telephone technical support. Advanced warranty exchange. Ground shipment both ways. Pricing is limited to the continental USA