


**P91g 1-3kVA UPS Price List**

\*For the most current pricing, visit [www.xpcc.com/pricing](http://www.xpcc.com/pricing)

**Online 1000VA-3000VA**  
208/230VAC

**Premium power protection for mission critical applications**

- › High output power factor
- › Up to 98% efficient operation
- › Extended battery packs available for 2U models
- › Multiple communications capability
- › Hot swappable battery design
- › Programmable Outlet Group (2U)
- › \$50,000 load protection policy
- › CE, RoHS, TAA compliant (UPS only)
- › 3 years electronics, 3 years battery warranty (USA and Canada)



**P91g Series 230V 50/60Hz**

Model	Part Number	Description	List Price	Input Power Cord	Output Receptacles	Unit Weight	Unit & Shipping Dimensions* (W x D x H)
P91gc-1000	90000746	1000VA/800W 208/230V UPS with 1A Charger, 1U	\$1,090.00	C14 inlet, 8ft L6-20P to C13 line cord	(3) C13	28 lbs	17.2" x 17.8" x 1.7" 22.5" x 24.5" x 6.5"
P91g-1500	90000747	1500VA/1500W 208/230V UPS with 2A-12A charger, 2U	\$1,469.00	C14 inlet, 8ft L6-20P to C13 line cord	(8) IEC C13	34.2 lbs	17.2" x 15.1" x 3.5" 23.6" x 19.7" x 9.45"
P91g-2000	90000748	2000VA/2000W 208/230V UPS with 2A-12A charger, 2U	\$1,929.00	C20 inlet, 8 ft L6-20P to C19 line cord	(8) IEC C13	43 lbs	17.2" x 19" x 3.5" 22.2" x 27.6" x 9.45"
P91g-3000	90000749	3000VA/3000W 208/230V UPS with 2A-8A charger, 2U	\$2,579.00	C20 inlet, 8 ft L6-20P to C19 line cord	(1) IEC C19 + (8) IEC C13	60.6 lbs	17.2" x 23.8" x 3.5" 23.6" x 30.5" x 9.45"

\*Rack depth is front bracket to unit panel. Add 1" for depth including front bezel. Capacity derates to 90% at 208 output.

**P91g Battery Packs**

Model	Part Number	Description	List Price	Unit Weight	Unit & Shipping Dimensions* (W x D x H)
P91-BP36	90000787	36V Battery Pack for P91g-1500, 2U	\$950.00	58.1 lbs	17.2" x 18.9" x 3.5" 22.2" x 27.6" x 9.45"
P91-BP36E	90000788	36V 4 String Extended Battery Pack for P91g-1500, 2U	\$1,380.00	104.4 lbs	17.2" x 23.6" x 3.5" 23.6" x 29.9" x 9.45"
P91-BP48	90000789	48V Battery Pack for P91g-2000, 2U	\$1,130.00	74.6 lbs	17.2" x 18.9" x 3.5" 27.6" x 22.2" x 9.45"
P91-BP72	90000790	72V Battery Pack for P91g-3000, P91g-3000, 2U	\$1,350.00	104.4 lbs	17.2" x 23.6" x 3.5" 23.6" x 29.9" x 9.45"

\*Rack depth is front bracket to unit panel. Add 1" for depth including front bezel.

**P91g Output Cords**

Model	Description	Cord Length	Input Voltage	List Price	Unit Weight
XPC-C14-615R	IEC C14 to 6-15R for use with P91cg-1000, P91g-1500, P91g-2000, P91g-3000	1ft	208/230V	\$45.00	3 lbs
XPC-C14-620R	IEC C14 to 6-15/20R for use with P91cg-1000, P91g-1500, P91g-2000, P91g-3000	1ft	200-240V	\$49.00	2 lbs
XPC-C14-L620R	IEC C14 to L6-20R for use with P91cg-1000, P91g-1500, P91g-2000, P91g-3000	1ft	200-240V	\$69.00	2 lbs
XPC-C14-L630R	IEC C14 to L6-30R for use with P91cg-1000, P91g-1500, P91g-2000, P91g-3000	1ft	200-240V	\$69.00	2 lbs
XPC-ZLC20-620R	Locking IEC C20 to 6-15/20R for use with P91g-3000	1ft	208/230V	\$79.00	3 lbs
XPC-ZLC20-L620R	Locking IEC C20 to L6-20R for use with P91g-3000	1ft	208/230V	\$79.00	3 lbs
XPC-ZLC20-L630R	Locking IEC C20 to L6-30R for use with P91g-3000	1ft	208/230V	\$79.00	3 lbs

**P91g Mounting Kits**

Model	Part Number	Description	List Price	Unit Weight	Unit Dimensions (W x D x H)
P90-RAIL	90000909	4-Post Rail Kit	\$148.50	5 lbs	3.8" x 19.8" x 2.8"
XPC-2PRAIL	90000406	2-Post Rail Kit; Rated for 125 lbs	\$102.00	5 lbs	4.0" x 20.0" x 3.0"
XPC-2POSTL	90000116	2-Post Shelf Kit; Rated for 150 lbs	\$160.00	9 lbs	21.5" x 23.3" x 3.5"
XPC-2PRLV2	90001273	2-Post 2U Center Mount with Front Ears; Rated for 160 lbs	\$225.00	11 lbs	16" x 15" x 9"
PV-WMB	90000392	Wall Mount Bracket (2U units)	\$80.00	5 lbs	4.0" x 24.0" x 4.0"
P90-FRMB	90000377	Front Rackmount Bracket for P91g-1000, 1500, 2000	\$39.00	1 lb	0.9" x 2.0" x 3.4"

**P91g Connectivity**

Model	Part Number	Description	List Price	Unit Weight	Shipping Dimensions (W x D x H)
SNMP-2PV3	90000741	Two Port Internal SNMP Card	\$389.00	1 lb	7.25" x 6" x 2.5"
SNMP-EMPV2*	90000674	Environmental Monitoring Sensor	\$230.00	1 lb	7.25" x 6" x 2.5"
MODBUS-IN	90000267	Modbus Card	\$319.00	1 lb	7.25" x 6" x 2.5"
RELAY-MINI	90000265	General Relay Contacts with DB9 & Terminal Block Adapter	\$120.00	1 lb	7.25" x 6" x 2.5"

\*SNMP-EMPV2 to be used with SNMP-2PV3

**Bypass Distribution Modules**

Model	Part Number	Description	List Price	Utility Input	Output Connections	UPS Connections	Unit Weight	Unit Dimensions (W x D x H)
XBDM1020HV2	90000094	Bypass 16A capacity for use with P91g-3000 (includes (2) IEC C20 C19 cord kit)	\$495.00	IEC C20 inlet	(2) IEC C19 + (4) IEC C13 front (4) IEC C13 back	IEC C20	3.5 lbs	19.3" x 3.5" x 1.75"

**Power Distribution Units & Transformers**

Model	Part Number	Description	List Price	Input Power Cord	Outlets	Unit Weight	Unit Dimensions (W x D x H)
XPDU-IEC	90000053	230V Basic Power Distribution Unit for use with P91g-3000	\$205.00	IEC C20 inlet	(10) IEC C13 + (2) IEC C19	2.6 lbs	19.0" x 3.5" x 1.75"
XAT-400	90000269	400VA Step Down Transformer 208V to 120V for use with P91g-1500, P91g-3000	\$660.00	208V IEC C14, 2ft	120V 5-15R, 2ft	8 lbs	7.0" x 6.8" x 5.9"
XPD-IT15A	90000739	1.5kW Transformer PDU 208V to 120V	\$1,090.00	Detachable 3 ft, C14 to C13 Cord	(16) 5-15R	43 lbs	17.3 x 10.5 x 3.5 in (2U)

**P91g Service Plans (USA and Canada)**

Model	Part Number	Description	List Price
P905SP15	90000522	Extended 5 Year Factory Warranty for P91g-1500, P91gc-1000, P91g-1000, P91g-1500	\$375.00
P905SP23	90000523	Extended 5 Year Factory Warranty for P91g-2000, P91g-3000	\$610.00
P90L5SPBP	90000524	Extended 5 Year Factory Warranty for P90-BP36, P90-BP36E, P90-BP48, P90-BP72	\$320.00

**Standard 3 Year Factory Warranty** – 3 years electronics/battery. Telephone technical support. Depot exchange. Ground shipment one way.

**Extended 5 Year Factory Warranty** – 5 year electronics/battery. Telephone technical support. Advanced exchange. Pricing is limited to the continental USA. Ground shipment both ways.

**P91g Battery Runtimes**

Runtimes are shown in minutes and will vary based on battery condition, age, cycles, and ambient temperature.

Model	Internal batteries		1		2		3		4		5		6		7		8	
	50%	100%	50%	100%	50%	100%	50%	100%	50%	100%	50%	100%	50%	100%	50%	100%	50%	100%
Percentage load:	50%	100%	50%	100%	50%	100%	50%	100%	50%	100%	50%	100%	50%	100%	50%	100%	50%	100%
P91gc-1000	20	8	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
P91g-1500 (BP36)	10	3	42	17	84	33	120	51	157	72	199	93	244	112	289	128	339	146
P91g-1500 (BP36E)	10	3	84	33	157	72	244	112	339	146	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
P91g-2000 (BP48)	10	3	42	17	84	33	121	51	157	72	200	93	244	112	290	128	340	147
P91g-3000 (BP72)	10	3	42	17	84	33	121	52	158	73	201	94	246	112	292	129	343	148

Maximum of eight battery packs per P91g-1500, P91g-2000, or P91g-3000 (excluding BP36E). Runtimes are shown in minutes and will vary based on battery condition, age, cycles, and ambient temperature.