SPDU

Switched & Metered-by-Outlet PDU
120V

Remote-monitored power distribution available in 6 and 14-outlet models.

- Individually controllable outlets for remote reboot
- Wall, desktop, or rack-mount installation
- LCD displays real-time data, alarms, and outlet status
- Per-outlet power monitoring for detailed energy visibility

J40 & J40i

ULTRA-SLIM SURGE PDU
120V or 230V

Protect AV, digital signage, kiosks, and POS from transients with ultra-slim J40 PDU

- Slim (1.2”) J40 mounts behind displays and in tight spaces
- Over voltage and over temperature MOV protection
- Power reset button allows manual cycling of power

XPDU / ISOLATION PDU

POWER DISTRIBUTION
1.5kVA to 10kVA

Rack power distribution for data centers and network closets.

- 120VAC and 208/230VAC
- Isolation models provide 240/120VAC
- Hardwire or Plug & Receptacle
- Wall mount and 1U/2U rack mounting

TXVR

3.8kVA-10kVA

ISOLATED ONLINE VOLTAGE REGULATOR
208VAC, 240/120V or 230/115V

Power conditioning for voltage critical processes in the most demanding conditions

- TXVR maintains output voltage at +/-1% with input variations of –45% to +45%
- Galvanic Isolation protects load from common mode noise
- TXVR is upgradable to a UPS by upgrading firmware and adding battery cabinets

JX Series

200W
POWER CONDITIONER
120V

Power conditioner for critical electronic equipment

- Complete line isolation, noise filtering, and enhanced surge suppression
- Brackets allows JX to mount on walls, under counters, or inside enclosures.
- Optional DIN Rail mounting

XBDM

BYPASS DISTRIBUTION
15, 20, 30, 63A

Repair or replace your UPS without power interruption by manually transferring critical loads from UPS power to utility power using the XBDM.

- Simplifies UPS repair or replacement and reduces costly downtimes
- Offers surge protection during UPS and utility mode
- Plug/receptacle and hardwired models available
- The ideal solution to reduce costly downtime; read the white paper at www.xpcc.com/whitepaper

POWER PROTECTION FOR SINGLE PHASE MISSION CRITICAL APPLICATIONS

Established in 2006, Xtreme Power manufactures UPS, and power distribution units for a global network of OEMs and distributors

Configure your UPS applications using our UPS selector:
www.xpcc.com/selector

For the most up to date flyers and documentation, please visit our website at:
www.xpcc.com

Additional resources available at:
www.xpcc.com/resources

For all three-phase products,reference our three-phase brochure.

Listings & certifications do not apply to all models

XPC USA Denver, CO / Tel (800) 582-4524 / sales@xpcc.com

© 2024 Xtreme Power Conversion Corporation
All rights reserved. ALL.01U (03/1/24)

XTREME POWER CONVERSION

SINGLE-PHASE CRITICAL POWER SOLUTIONS

Power Conversion®

A60
550VA & 850VA
STANDBY UPS
120V

Affordable, reliable power protection for valuable home and small business electronics

- Compact design allows for horizontal or vertical placement
- Touch LCD (850VA only)
- Auto restart after full discharge
- USB communications and USB charging port
- 3 year warranty

S71
700VA–1500VA
LINE INTERACTIVE UPS
120V

Equip your office with reliable battery backup and protection from power outages

- Touch LCD display monitors UPS vitals
- Wide operating voltage means longer battery life
- USB HID port
- Auto restart
- Automatic Voltage Regulation (AVR)

P91 5-10kVA
5, 6 & 10kVA
ONLINE UPS
208/230V or 208/120V

High density rack UPS for data center and edge applications

- Unity output power factor (kVA = KW) for high density loads
- Optional maintenance bypass with configurable receptacles
- Tower, 2-post, and 4-post rack mounting configurations available

M90S
6kVA-24kVA
MODULAR ONLINE UPS
208/120V or 240/120V

Scalable, Modular, Configurable UPS for Continuous Power Availability

- Unity output power factor for high density loads
- 2, 4 & 6 slot UPS & battery enclosures available.
- Standard internal maintenance bypass and optional receptacle panels
- Up to 98% efficiency for lowest operation cost

J60 & J60i
350VA & 600VA
LITHIUM-ION UPS
120V or 230V

World's smallest & lightest UPS

- Up to 15-year battery life
- Ultra-slim for mounting in small spaces
- UL, CE, RoHS, TAA, UN38.3
- 5-year warranty
- Applications: POS terminals, wireless access points, kiosks, signage

P80 & P80g
800VA–5kVA
LINE INTERACTIVE UPS
120V or 208/230V

Advanced pure sine wave line interactive power protection for servers and network equipment

- 0.9 output power factor for high density loads
- 99% efficiency in ECO mode
- Rack, tower and wall mounting
- Extended battery packs available for 1500VA-5kVA models

T91
700VA–3000VA
ONLINE TOWER UPS
120V or 208/230V

Unity power factor tower UPS provides high density online power protection for unstable power conditions

- Up to unity output power factor (kVA = kW) for high density loads
- Fast recharge time: up to 95% in just 3 hours
- Extended battery packs available for runtimes up to 24 hours

M90S-12S
6kVA-48kVA
MODULAR ONLINE UPS
208/120V or 240/120V

Protect edge data centers and large homes with a modular M90S- 12S UPS for single-phase applications up to 48kVA

- Universal slots accept power or battery modules
- 10" LCD display
- Modular for capacity or N+1 redundancy
- Unity output power factor

J60C & J60Ci
600VA
LITHIUM-ION UPS
120V or 230V

Lithium-ion 8.5"-deep 1U UPS ideal for short-depth racks.

- Up to 15-year battery life
- Web/SNMP for remote monitoring and on/off control
- Rack, tower, or wall-mount installation
- UL, CE, RoHS, TAA, UN38.3
- 5-year warranty
- Applications: signage, kiosks, automation

J90 & J90i
1000VA – 3000VA
LITHIUM-ION
ONLINE UPS
120VAC or 208/230V

Online 1U UPS with Individual Receptacle Control

- True double conversion online topology
- Remote receptacle control via web/snmp
- Hot swappable battery design
- Lithium Iron Phosphate (LFP) provides longest battery life
- Extended runtimes (2 & 3kVA models)
- 6 year warranty

P91 & P91g
1000VA – 3000VA
LEAD ACID & LITHIUM-ION
ONLINE UPS
120VAC or 208/230V

Premium power protection for mission critical applications

- Unity Power Factor Output (Lead Acid)
- Fast recharge
- Battery charge current from 1A to 8A
- Hot swappable battery design
- 3 year warranty (Lead Acid)
- 6 year warranty (Lithium)

TX91 & TX91L
3.8kVA-10kVA
ISOLATED ONLINE UPS
240/120V or 230/115V

Isolated online UPS & Power Conditioner provide the cleanest power in the most demanding conditions

- Unity output power factor for high density loads
- Integral maintenance bypass and optional PDU
- Galvanic Isolation protects load from common mode noise
- Matching battery cabinet for longer runtimes

For detailed specs on all our products, visit www.xpcc.com