

XTREME POWER CONVERSION Basic XPDU

Basic Rack Power Distribution // 15A to 50A

For more information, visit www.xpcc.com/xpdu



Rack power distribution solutions designed to meet the needs of any data center or wiring closet

Improve data center power distribution with the XPDU family, a series of power distribution units that combine the key features needed to manage high density equipment racks or wiring closets.

XPDU's deliver reliable power distribution to multiple units of connected equipment by adding up to 24 receptacles to your rack space. These PDU's compliment your current power source and are compatible with any manufacturer's UPS.

For IP addressable PDU reference the SPD at www.xpcc.com/spd and for surge PDU's reference the XPDS at www.xpcc.com/xpds

PRODUCT SNAPSHOT

- › Available 120V models: 15A, 20A
- › Available 208/230V & 240/120V models: 30A, 50A
- › Vertical and horizontal configurations
- › 3 year full warranty (USA and Canada)

FEATURES

Plug and power—XPDU's provide up to 24 receptacles for power distribution

Branch circuit protection—UL1077 listed output circuit breaker

Hardwired models—input pigtail available with basic 50A XPDU models

Mounting options—horizontal or verticle rack mounting (0U rack space)

NEMA plugs and IEC inlet—multiple input configurations available

MODEL SELECTION GUIDE

For more information, visit www.xpcc.com/xpdu

MODEL NUMBER	Input Power Connection	Outlets	Voltage	Amperage	Dimensions (W x D x H)	Weight
Basic PDU - 15A & 20A models						
XPD815HV	12 ft, 5-15P	(8) 5-15R	120V	15A	17 x 3.75 x 1.7 in (1U)	2.6 lbs
XPD1415HV	12 ft, 5-15P	(14) 5-15R	120V	15A	17 x 3.75 x 1.7 in (1U)	3.5 lbs
XPD1420HV	12 ft, L5-20P*	(14) 5-15/20R	120V	20A	17 x 3.75 x 1.7 in (1U)	4.8 lbs
XPDU-IEC	IEC C20 inlet	(2) IEC C19 + (10) IEC C13	208/230V	15/20A	17 x 3.75 x 1.7 in (1U)	4.4 lbs
Basic PDU - 30A & 50A models						
XPD24C13V	6 ft, L6-30P	(24) C13	208/230V	30A	66.0 x 1.8 x 1.8 in (vertical)	12.0 lbs
XPD31	6 ft, L6-30P	(2) L6-30R + (2) L6-20R + (4) 6-15/20R	208/230V	30A	19.0 x 4.7 x 3.5 in (2U)	9.0 lbs
XPD32	6 ft, L6-30P	(2) L6-30R + (4) L6-20R	208/230V	30A	19.0 x 2.4 x 3.5 in (2U)	7.5 lbs
XPD33	6 ft, L6-30P	(4) IEC C19 + (8) IEC C14	208/230V	30A	19.0 x 2.4 x 3.5 in (2U)	6.0 lbs
XPD34	6 ft, L14-30P	(2) L6-30R + (4) L6-20R + (12) 5-20R	240/120V	30A	19.0 x 4.7 x 3.5 in (2U)	9.5 lbs
XPD35	3ft, Hardwired pigtail	(2) L6-30R + (4) L6-20R	208/230V	50A	19.0 x 2.4 x 3.5 in (2U)	7.0 lbs
XPD36	3ft, Hardwired pigtail	(4) IEC C19 + (8) IEC C14	208/230V	50A	19.0 x 2.4 x 3.5 in (2U)	6.8 lbs
XPD37	3ft, Hardwired pigtail	(2) L6-30R + (4) L6-20R + (12) 5-20R	240/120V	50A	19.0 x 4.7 x 3.5 in (2U)	10.0 lbs
XPD38	6ft, L14-30P	(4) L5-30R + (4) L5-20R	120V	30A	19.0 x 4.7 x 3.5 in (2U)	9.5 lbs
XPD39	3ft, Hardwired pigtail	(4) L5-30R + (4) L5-20R	120V	50A	19.0 x 4.7 x 3.5 in (2U)	10.0 lbs

*Ships with an L5-20R to 5-20P adapter



XPD34 rear view



XPD34 front view

X-TREME
Power Conversion®

Protect your business.

XPC USA / Denver, CO / sales@xpcc.com

www.xpcc.com

©2020 Xtreme Power Conversion Corporation. All Rights Reserved. XPDU.01U (Rev 3/17/21)