

# XTREME POWER CONVERSION P80 // TRIPP LITE SMART2200RML2U COMPARISON

The P80 is a high level line interactive UPS with industry leading reliability, efficiency, and flexibility. The P80 products are available in 120V capacities from 800VA to 3000VA, with 208V models in 3KVA and 5KVA sizes.



## UPS COMPARISON

	XTREME POWER P80-2200	TRIPP LITE SMART2200RML2U	ADVANTAGES
Capacity	2200VA/2000W	2200VA/1920W	Xtreme Power P80 has a higher output wattage rating for more usable power on the output, especially when considering that the Tripp Lite unit derates to 1600W when an EBM is used.
Topology	Line Interactive	Line Interactive	Both the Xtreme Power P80 and the Tripp Lite SmartPro have Line Interactive topology with Automatic Voltage Regulation (AVR) with sinewave output, providing clean and reliable network grade power.
Form Factor	Tower mounts included Optional 2U rack, or wall mount	2U Rack Optional tower or wall mount	Both Xtreme Power and Tripp Lite provide 2U rack, tower or wall mounting providing a high level of mounting versatility.
Hot Swappable Batteries	Yes	Yes	Both Xtreme Power and Tripp Lite provide hot swappable batteries ensuring clean, uninterrupted power to protected equipment while batteries are being replaced.
Extended Runtime	(2) EBPs	(1) EBP with 20% derating	Xtreme Power P80-2200 with (2) EBPs can provide up to 58 minutes runtime at full load. Tripp Lite is limited to (1) EBP and derates the UPS by 20% when EBP is added.
Software	Standard	Downloadable from web	Xtreme Power provides a CD with the UPS containing monitoring and shutdown software. Tripp Lite requires you to download the software from their website.
Warranty	3 years	2 years standard, 3 years with registration	Xtreme Power P80 warranty covers a full 3 years for both the UPS and batteries. Tripp Lite provides 2 years warranty and can be extended to 3 years with registration. Tripp Lite EBPs carry only a 2 year warranty.