

XTREME POWER CONVERSION V70-1000 UPS // CyberPower OR1000LCDRM1U COMPARISON

Both UPS systems provide line-interactive, 120 V power protection in a shallow 1U form factor for AV, network, and security applications. The key differences are mounting flexibility, usable watt capacity, visibility, remote management, and procurement readiness, with the V70-700 designed for space-constrained and regulated installations.



UPS COMPARISON

Feature	Xtreme Power V70-1000	CyberPower OR1000LCDRM1U	V70 Advantage
Topology	Line-interactive UPS with AVR	Line-interactive UPS with AVR	Comparable line-interactive AVR protection
Capacity	1000VA/600W	1000VA/600W	Equivalent 1000 VA / 600 W rating
Form Factor / Mounting	2U rack-mount, wall mount or tower	1U rack-mount. No tower or wall mounting	Tower and Wall-mount flexibility
Power Cord	10 ft with right angle 5-15P Plug	10 ft with right angle 5-15P Plug	Longer, right-angle cord simplifies routing
Dimensions (W x D x H)	17.3" x 9" x 3.4"	17.3" x 15.3" x 1.75"	Significantly shallower depth
Communication Ports	USB (HID), RS-232, and Optional Web/SNMP	USB (HID), RS-232, and Optional Web/SNMP	Similar capabilities
Surge / Transient Protection	Standard surge and line protection	Standard surge and line protection	Comparable surge protection
TAA	TAA-compliant	Not TAA-compliant	Meets federal procurement requirements
Warranty	3 years (electronics & battery)	3 years	Similar capabilities