

XTREME POWER CONVERSION V70-1000 // Minuteman PRO1500RT2U / PRO1500RTNC COMPARISON

Both are line-interactive UPS platforms for edge and IT loads. V70-1000 prioritizes higher capacity, compact size, shallow depth, wall mounting, and TAA compliance, while Minuteman PRO1000RT emphasizes higher watt output and runtime, with optional or bundled network management.



1000 VA Line-Interactive UPS Comparison

Feature	Xtreme Power Conversion V70-1000	Minuteman PRO1000RT2U / PRO1000RTNC	V70 Advantage
UPS Topology	Line-interactive with AVR	Line-interactive with AVR	Comparable
Capacity	1000VA / 600W	1000VA / 700W	Minuteman has higher capacity
Form Factor	Rack, wall, or tower (included)	Rack / tower; wall optional	Wall mount included
Output Waveform (Battery)	Simulated sine wave	Simulated sine wave	Equivalent
Runtime (700W Load)	~5 minutes	~4 minutes	Longer runtime
Surge & Noise Protection	Surge suppression and EMI/RFI filtering	Surge suppression and EMI/RFI filtering	Equivalent
Communications	LCD, USB (HID), RS-232, optional Web/SNMP	LCD, USB (HID), RS-232, optional or bundled Web/SNMP (RTNC)	Equivalent
Power Cord	Right-angle 5-15P, 10 ft	Straight 5-15P, 10 ft	Better rack clearance
Dimensions (Depth)	9.0"	16.1"	Much shallower
Compliance	UL, cUL, RoHS, TAA	UL, cUL, RoHS	TAA compliant
Warranty	3 years	3 years	Equivalent