

XTREME POWER CONVERSION V70-1500 UPS // CyberPower CP1500PFCRM2U COMPARISON

Both systems are shallow-depth, 1500 VA line-interactive UPS platforms designed to protect entry-level servers, network closets, retail POS, and VoIP equipment. While performance is broadly comparable, the V70-1500 differentiates with broader mounting flexibility and full TAA compliance, making it better suited for space-constrained and federally regulated installations.



UPS COMPARISON

Feature	Xtreme Power V70-1500	CyberPower CP1500PF-CRM2U	V70 Advantage
Topology	Line-interactive UPS with AVR	Line-interactive UPS with AVR	Comparable AVR protection
Capacity	1500VA/900W	1500VA/1000W	CyberPower supports slightly higher watt load
Battery Runtime	3 minutes	3.1 minutes	Comparable Runtime
Waveform (on battery)	Simulated Sinewave	PFC Sinewave	Sinewave preferred for highly sensitive loads
Form Factor / Mounting	2U rack, wall mount, or tower (hardware included)	2U rack or tower	True wall-mount support + broader install flexibility
Power Cord	10 ft with right angle 5-15P Plug	6 ft with straight 5-15P Plug	Easier routing in racks & cabinets
Output Receptacles	(8) NEMA 5-15R	(8) NEMA 5-15R	Equivalent
Dimensions (W x D x H)	17.3" x 10.5" x 3.4"	17.0" x 10.5" x 3.4"	Comparable Footprint
Communication / Management	LCD, USB (HID), RS-232, and Optional Web/SNMP	LCD, USB (HID), Serial and Web/SNMP	Comparable monitoring options
TAA	TAA-compliant	Not TAA-compliant	Eligible for federal procurement
Warranty	3 years (electronics & battery)	3 years	Comparable Warranty