

XTREME POWER CONVERSION V70-1500 // Minuteman PRO1500RT2U / PRO1500RTNC COMPARISON

Both systems protect servers, POS, and network equipment using line-interactive topology. V70-1500 prioritizes higher capacity, compact footprint, shallow depth, and installation flexibility, while Minuteman PRO1500RT focuses on higher watt output and longer runtime in a much deeper chassis.



1000 VA Line-Interactive UPS Comparison

Feature	V70-1500	PRO1500RT2U / PRO1500RTNC	V70 Advantage
UPS Topology	Line-interactive with AVR	Line-interactive with AVR	Comparable
Capacity	1500VA / 900W	1500VA / 1050W	Minuteman has higher capacity
Form Factor	Rack, wall, or tower (included)	Rack / tower; wall optional	Wall mount included
Output Waveform (Battery)	Simulated sine wave	Simulated sine wave	Equivalent
Runtime (Full Load)	~3 minutes	~4 minutes @ full load	Minuteman has more runtime
Surge & Noise Protection	Surge suppression and EMI/RFI filtering	Surge suppression and EMI/RFI filtering	Equivalent
Communications	LCD, USB (HID), RS-232, optional Web/SNMP	LCD, USB (HID), RS-232, optional or bundled Web/SNMP (RTNC)	Equivalent
Power Cord	Right-angle 5-15P, 10 ft	Straight 5-15P, 10 ft	Better rack clearance
Dimensions (Depth)	10.5"	20.1"	Dramatically shallower
Compliance	UL, cUL, RoHS, TAA	UL, cUL, RoHS	TAA compliant
Warranty	3 years	3 years	Equivalent